


1306 Reverse Mount Chip LED




Ligitek LG1306

High Intensity surface mount chip LED packages are now available from Plus Opto in Reverse Mountable 1306 package (1205 for the RGB) with typical intensities as below;-

Features include

- 1306 package, low profile 0.6mm in single colour
- Low power consumption, high efficiency
- Broad range of colours including RGB
- Compatible with automatic placement equipment
- 130° angle of emission
- Compatible with IR and vapor phase reflow solder process
- Low cost for High Brightness
- Supplied on 7" reels for auto-insertion

1306 Package Outline Dimensions



Note: 1. All dimension are in mm tolerance is ± 0.1 mm unless otherwise noted.

Applications include;-

- High Intensity for Message Board & Signage
- Low Cost White with High Output for instrumentation backlighting
- Ultra Bright for Alarm Panels
- Audio & Sound mixing desk

Samples available to ship from stock

1306 Size, Reverse Mount

Part No.	Emitted Colour	Wavelength λ (nm)	Intensity Iv (mcd)
LG-1306HRF-CT	Ultra Red	639	140
LG-1306DGM-CT	Ultra Green	525	360
LG-1306-9UG-CT	Bright Green	575	72
LG-1306HYS-CT	Ultra Yellow	591	112
LG-1306DBK-CT	Blue	468	72
LG-1306WK-DT	White	-	112
LG-1205RGB-CT	Full Colour RGB	624 525 468	100 200 65

[More information](#)

