







SP Series CC Mains Dimmable LED Drivers

| Picture | Model | Description | Certificates | Warranty |
|---|----------------------|---|-----------------------|----------|
|  | SNP10-350ILT | Input Voltage:180V-264V Output Power:10W Constant Output Current:350mA Load:6-10w PF:0.8 Dimension:L123xW44.6xH19.2mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According toEN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC;SAA;C-tick | 3 years |
|  | SNP10-450ILT | Input Voltage:180V-264V Output Power:10W Constant Output Current:450mA Load:8-10w PF:0.85 Dimension:L123.7xW45.7xH20.2mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According toEN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC;SAA;C-tick | 3 years |
|  | SP10-350ILT-1 | Input Voltage:180V-264V Output Power:10W Constant Output Current:350mA Load:2.8-10w PF:0.9 Dimension:L123xW44.6xH19.2mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According toEN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC;SAA;C-tick | 3 years |
|  | SP10-700ILT-1 | Input Voltage:180V-264V Output Power:10W Constant Output Current:700mA Load:2.8-10w PF:0.9 Dimension:L123xW44.6xH19.2mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According toEN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC;SAA;C-tick | 3 years |







SP Series CC Mains Dimmable LED Drivers

| Picture | Model | Description | Certificates | Warranty |
|---|--------------------|---|--------------|----------|
|  | SP15-350ILT | Input Voltage:198V-264V Output Power:15W Constant Output Current:350mA Load:7.5-15w PF:0.9 Dimension:L123xW45.6xH20.2mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According toEN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |
|  | SP15-500ILT | Input Voltage:198V-264V Output Power:15W Constant Output Current:500mA Load:7.5-15w PF:0.9 Dimension:L123xW45.6xH20.2mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According toEN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |
|  | SP15-700ILT | Input Voltage:198V-264V Output Power:15W Constant Output Current:700mA Load:7.5-15w PF:0.9 Dimension:L123xW45.6xH20.2mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According toEN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |
|  | SP18-350ILT | Input Voltage:198V-264V Output Power:18W Constant Output Current:350mA Load:9-18w PF:0.9 Dimension:L147.8xW46xH23mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According toEN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |







SP Series CC Mains Dimmable LED Drivers

| Picture | Model | Description | Certificates | Warranty |
|---|--------------------|---|--------------|----------|
|  | SP18-500ILT | Input Voltage:198V-264V Output Power:18W Constant Output Current:500mA Load:9-18w PF:0.9 Dimension:L147.8xW46xH23mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According to EN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |
|  | SP18-700ILT | Input Voltage:198V-264V Output Power:18W Constant Output Current:700mA Load:9-18w PF:0.9 Dimension:L142xW46xH23mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According to EN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |
|  | SP24-350ILT | Input Voltage:198V-264V Output Power:24W Constant Output Current:350mA Load:12-24w PF:0.95 Dimension:L157xW35.3xH23.5mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According to EN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |
|  | SP24-500ILT | Input Voltage:198V-264V Output Power:24W Constant Output Current:500mA Load:12-24w PF:0.95 Dimension:L157xW35.3xH23.5mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According to EN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |





SP Series CC Mains Dimmable LED Drivers

| Picture | Model | Description | Certificates | Warranty |
|---|---------------------|--|--------------|----------|
|  | SP24-700ILT | Input Voltage:198V-264V Output Power:24W Constant Output Current:700mA Load:12-24w PF:0.95 Dimension:L157xW35.3xH23.5mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According toEN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |
|  | SP24-1050ILT | Input Voltage:198V-264V Output Power:24W Constant Output Current:1050mA Load:12-24w PF:0.95 Dimension:L157xW35.3xH23.5mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According toEN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |
|  | SP36-350ILT | Input Voltage:180V-264V Output Power:36W Constant Output Current:350mA Load:15--30w PF:0.95 Dimension:L167xW41xH29mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According toEN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |
|  | SP36-500ILT | Input Voltage:180V-264V Output Power:36W Constant Output Current:500mA Load:18-36w PF:0.95 Dimension:L167xW41xH29mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According toEN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |



SP Series CC Mains Dimmable LED Drivers

| Picture | Model | Description | Certificates | Warranty |
|---|---------------------|--|--------------|----------|
|  | SP36-700ILT | Input Voltage:180V-264V Output Power:36W Constant Output Current:700mA Load:18-36w PF:0.95 Dimension:L167xW41xH29mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According to EN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |
|  | SP36-1050ILT | Input Voltage:180V-264V Output Power:36W Constant Output Current:1050mA Load:18-36w PF:0.95 Dimension:L167xW41xH29mm Open Circuit;Short Circuit;Over Load;Over Heat Protection Safety According to EN61347-1,EN61347-2-13 EMI&EMS According to EN55015; EN61000-3-2;EN61000-3-3;EN61547 | CE;TUV;EMC | 3 years |

T +44 (0) 1942 671122 **F** + (0) 1942 671133 **E** sales@plusopto.co.uk **W** www.plusopto.co.uk
 B13 Derwent Court William Way Moss Industrial Estate Leigh Lancashire WN7 3PT

QR-MAR-018B